

折弯机技术参数 TABLE OF TECHNICAL PARAMETERS FOR Bending machine (press brake)

WC67Y/WC67K系列

型号 Type	公称压力 Nominal pressure (KN)	工作台长度 Bench length (mm)	主柱间距 Pole distance (mm)	喉口深度 Throat depth (mm)	滑块行程/ 行程次数 Slipper stroke/ Stroke times (mm/min)	最大开启高度 Max opening height (mm)	主电机功率 Main motor power (KW)	外形尺寸 Dimension L×W×H (mm)
40/2200	400	2200	1600	200	100/10	320	5.5	2300×1100×1900
40/2500	400	2500	1900	200	100/10	320	5.5	2600×1100×1900
50/2200	500	2200	1600	200	100/10	320	5.5	2300×1150×1940
50/2500	500	2500	1900	200	100/10	320	5.5	2600×1150×1940
63/2500	630	2500	1900	250	120/10	380	5.5	2600×1600×2300
63/3200	630	3200	2600	250	120/10	380	5.5	3300×1600×2300
80/3200	800	3200	2600	320	120/10	380	7.5	3300×1700×2300
80/4000	800	4000	3100	320	120/10	380	7.5	4100×1700×2300
100/3200	1000	3200	2600	320	120/5	380	7.5	3300×1800×2400
100/4000	1000	4000	3100	320	120/8	380	7.5	4100×1800×2400
160/3200	1600	3200	2600	320	200/6	450	11	3300×1600×2600
160/4000	1600	4000	3200	320	200/6	450	11	4100×2000×2600
160/6000	1600	6000	4800	320	200/6	450	11	6100×2000×3200
200/3200	2000	3200	2600	320	200/3	500	11	3300×2100×2600
200/4000	2000	4000	3100	320	200/3	500	11	4100×2100×2600
200/5000	2000	5000	4000	320	200/3	500	11	5100×2100×3000
250/4000	2500	4000	3200	350	250/3	550	18.5	4100×2200×3500
250/5000	2500	5000	4000	350	250/3	550	18.5	5100×2200×3500
250/6000	2500	6000	4800	350	250/3	550	18.5	6100×2200×3500
300/5000	3000	5000	4000	400	250/3	550	22	5100×2600×4000
300/6000	3000	6000	5000	400	250/3	550	22	6100×2600×4200
300/7000	3000	7000	5620	400	250/3	550	22	7100×2600×4400
320/7000	3200	7000	5620	400	250/2.5	600	22	7100×2600×4400
350/6000	3500	6000	5100	450	250/2.5	680	30	6100×2600×4200
350/7000	3500	7000	5620	450	250/2.5	680	30	7100×2500×4500
400/4000	4000	4000	3100	350	300/2.5	620	30	4100×2700×3800
400/6000	4000	6000	4820	400	320/2.5	620	30	6100×2800×4200
400/6500	4000	6500	5100	400	320/2.5	620	30	6100×2800×4300
500/5000	5000	5000	4100	400	320/2.5	630	37	5100×3000×4400
500/6000	5000	6000	4820	400	320/2.5	630	37	6100×3000×4700
500/7000	5000	7000	5620	400	320/2.5	630	37	7100×3000×4900
600/6000	6000	6000	4820	400	320/2.5	630	37	7100×2965×4900
600/7000	6000	7000	5620	400	320/2.5	630	37	6100×2965×4700

2-WC67K系列双机联动数控板料折弯机

2-WC67K DOUBLE UNIT CNC PLATE BENDERS

性能特点

- ◆选用两台WC67K系列同规格主机，配置双机联动同步装置；
- ◆两台机床联动可加工特长工件；
- ◆两台机床还可以同时单独使用，提高生产效率，配有挠度补偿机构；
- ◆同步机构采用液压伺服和机械挡块，上滑块行程和后挡料架位置采用机动快速调节，手动微调，电子数显控制。

Features

Two WC67K series in same specification are chosen as main machine with double motor linkage synchro-device which may work together to process overlong workpiece or operate separately to increase production efficiency. Deflection compensation device is fitted, too. Mechanic and fluid servos with mechanic slider are utilized in synchronous device. The stroke of upper slider and the position of rear apron are regulated quickly by machine and micro-regulated by hand with electronic NC display.



型号 Type	公称压力 Nominal pressure (KN)	工作台长度 Bench length (mm)	主柱间距 Pole distance (mm)	喉口深度 Throat depth (mm)	滑块行程 Slipper stroke (mm/min)	行程次数 Stroke times (mm/min)	最大开启高度 Max opening height (mm)	主电机功率 Main motor power (KW)	外形尺寸 Dimension L×W×H (mm)
2-WC67K-200/5000	2000	5000	4100	320	200	≥3	465	11	5100×2100×3000
2-WC67K-250/5000	2500	5000	4000	350	250	≥3	560	18.5	5100×2200×3500
2-WC67K-250/6000	2500	6000	5000	350	250	≥3	560	18.5	6100×2200×3500
2-WC67K-300/5000	3000	5000	4100	400	250	≥3	600	22	5100×2600×4000
2-WC67K-300/6000	3000	6000	5000	400	250	≥3	600	22	6100×2600×4200
2-WC67K-300/7000	3000	7000	5620	400	250	≥3	600	22	7100×2600×4400
2-WC67K-350/6000	3500	6000	5100	450	250	≥2.5	680	30	6100×2600×4200
2-WC67K-350/7000	3500	7000	5620	450	250	≥2.5	680	30	7100×2500×4500
2-WC67K-400/6000	4000	6000	4820	400	320	≥2.5	620	30	6100×2800×4200
2-WC67K-400/6500	4000	6500	5100	400	320	≥2.5	620	30	6100×2800×4300
2-WC67K-500/5000	5000	5000	4100	400	320	≥2.5	630	37	5100×3000×4400
2-WC67K-500/6000	5000	6000	4820	400	320	≥2.5	630	37	6100×3000×4700
2-WC67K-500/7000	5000	7000	5620	400	320	≥2.5	630	37	7100×3000×4900