

剪板机技术参数

TABLE OF TECHNICAL PARAMETERS FOR SHEARING MACHINES

QC12Y/QC12K系列

型号 Type	可剪规格 Plate size (mm)	剪切角度 Shear angle (°)	行程次数 Stroke times (min ⁻¹)	后挡料距离 Extruded-plate length (mm)	主电机功率 Main motor power (KW)	外形尺寸 Dimension L x W x H (mm)
4x2500	4x2500	1.5	18	20-500	4	3200x1650x1620
4x3200	4x3200	1.5	14	20-500	5.5	3900x1650x1620
4x4000	4x4000	1.5	12	20-500	5.5	4700x1900x1800
4x5000	4x5000	1.5	10	20-800	7.5	5700x2100x2200
4x6000	4x6000	1.5	8	20-750	7.5	6460x2100x2200
6x2500	6x2500	1.5	18	20-500	7.5	3200x1650x1620
6x3200	6x3200	1.5	14	20-500	7.5	3900x1650x1620
6x4000	6x4000	1.5	12	20-500	7.5	4700x1850x1700
6x6000	6x6000	1.5	8	20-800	11	6700x2200x2200
8x2500	8x2500	1.5	14	20-500	7.5	3200x1650x1620
8x3200	8x3200	1.5	12	20-500	7.5	4000x1650x1620
8x4000	8x4000	1.5	10	20-500	7.5	4800x1800x1700
8x5000	8x5000	1.5	8	20-800	11	5700x2250x2310
10x2500	10x2500	1.5	10	20-500	11	3200x1800x1700
10x3200	10x3200	1.5	10	20-500	18.5	3900x1950x1900
10x4000	10x4000	1.5	8	20-800	18.5	4700x2200x2100
10x6000	10x6000	1.5	6	20-800	18.5	6700x2500x2450
12x2500	12x2500	1° 40'	11	20-600	18.5	3200x2127x2235
12x3200	12x3200	1° 40'	10	20-600	18.5	3900x2127x2235
12x4000	12x4000	1.75°	8	20-800	18.5	4700x2250x2100
12x6000	12x6000	1.75°	5	20-800	30	6700x2700x2750
12x8000	12x8000	1.75°	5	20-800	37	9100x3400x2900
16x2500	16x2500	2.5°	8	20-600	18.5	3200x2400x2100
16x3200	16x3200	2.5°	7	20-600	22	4000x2400x2100
16x4000	16x4000	2.5°	6	20-800	22	4700x2500x2300
16x6000	16x6000	2.5°	6	20-800	37	6700x3300x2750
20x2500	20x2500	2.5°	6	20-800	37	3200x2100x2600
20x3200	20x3200	2.5	5	20-800	37	3900x2350x2750
20x4000	20x4000	2.5	4	20-800	37	4800x2400x2750
20x6000	20x6000	2.5	4	20-800	37	6700x3200x2860
25x2500	25x2500	3	5	20-800	37	3500x2400x2500
25x3200	25x3200	3	4	20-800	37	4000x2400x2500
25x4000	25x4000	3	3	20-800	37	4800x2400x2800
25x6000	25x6000	2.5	2	20-800	37	6700x3400x2860

Q11系列机械剪板机 MECHANICAL PLATE SHEARS



型号 Type	可剪板厚 Cutting thickness (mm)	可剪板宽 Cutting length (mm)	行程次数 Travel times (min ⁻¹)	剪切角 Cutting angle (°)	后挡料距离 Bumper distance (mm)	电机功率 Power (KW)	外形尺寸 Dimension L x W x H (mm)
3x1200	3	1200	20	2° 50'	350	3	2015x1500x1300
3x1300	3	1300	20	2° 50'	350	3	2115x1500x1300
3x1500	3	1500	20	2° 50'	350	3	2515x1500x1300
4x2000	4	2000	20	1° 30'	500	5.5	3200x1300x1610
4x2500	4	2500	20	1° 30'	500	5.5	3580x1300x1610
4x3200	4	3200	20	1° 30'	600	7.5	4380x1900x1600
4x4000	4	4000	20	1° 30'	600	7.5	4650x1820x1700
6.3x2000	6.3	2000	24	2°	500	7.5	3180x1765x1500
6x2500	6	2500	24	2°	500	7.5	3680x2200x2020
6x3200	6	3200	20	1° 45'	650	7.5	4300x2250x2150
8x2000	8	2000	24	2°	500	11	3180x1765x1500
8x2500	8	2500	20	2° 30'	650	15	3680x2250x2450
13x2500	13	2500	30	3°	700	11	3680x2330x2500
16x2500	16	2500	30	3°	700	22	3680x2800x2450
20x2500	20	2500	25	3°	750	22	3650x2800x2900